

ALL-FLO Pump Company, Inc.

9321 Pineneedle Drive • Mentor, Ohio 44060 • Tel (440) 354-1700 • Fax (440) 354-9466
www.all-flo.com email@all-flo.com

Here are a few reasons to consider ALL-FLO Air Operated Double Diaphragm Pumps

Quality – Reliability – Cost Reductions

- Patented, lube-free air valve system means no oil contamination of product and hassle free operation.
- Pump sizes from ¼ inch to 3 inch. 0 to 255 GPM.
- ALL-FLO's patented air valve won't stall at slow speeds.
- The air side of the pump is constructed of non-metallic materials. If a diaphragm ruptures or if fluid is spilled on the pump, these vital parts are not destroyed. Non-metallic air valve components are also much less prone to air valve icing when air lines contain water.
- No air leakage when fluid discharge valves are closed.
- All pumps are 100% tested prior to shipment.
- ALL-FLO pumps are designed with service in mind. Fewer parts and less down time keep maintenance costs low.
- All pumps built with PTFE elastomers have back-up Santoprene diaphragms. Santoprene is a highly resistant EPDM and polypropylene compound.
- Conductive models available.
- FDA and USDA rated materials are available.
- Five year warranty against defects in material and workmanship.
- Parts ship within 24 hours after receipt of order.
- Cost savings
- Modular design, band clamp and bolted construction provide ease of maintenance.