



AIR CYLINDERS				HYDRAULIC CYLINDERS		
NFPA STEEL HEAVY DUTY	NFPA ALUMINUM MED DUTY	METRIC STEEL HEAVY DUTY	METRIC ALUMINUM MED DUTY	NFPA HIGH PRESSURE	NFPA LOW PRESSURE	METRIC HIGH PRESSURE

DIMENSIONAL CHARTS	PRODUCT INFO SHEETS	CYLINDER ACCESSORIES	CYLINDER REPAIR DIVISION	FORD & DAIMLER CHRYSLER STANDARD CYLINDERS	AIR POWERED CLAMPS	PNEUMATIC THRUSTERS (SLIDES & DIE LIFTERS)	SPECIAL CYLINDERS	ABOUT US
--------------------	---------------------	----------------------	--------------------------	--	--------------------	--	-------------------	----------

- Request Product Literature
- Request Catalog on Disk
- Request Quote

When the pressure is on, You can count on Peninsular!

»HOME »EMAIL US »SITMAP

AIR CYLINDERS
Click links below to view pages in this section

- NFPA Steel Heavy Duty
- NFPA Aluminum Medium Duty
- Metric Steel Heavy Duty
- Metric Aluminum Medium Duty

Cylinder Warranties

- Hydraulic Cylinders
- Pneumatic Cylinders
- Custom Cylinders

Air Cylinders

» NFPA Steel Heavy Duty Air Cylinder-Model MH



High Quality Heavy Duty Long Lasting - Steel NFPA Air Cylinders

- » Steel / Pre-Lubricated
- » 250 psi / Heavy Duty

- Designed To Survive In Destructive Applications where other Air Cylinders have failed
- Internally Lubricated for Life (No In-Line Oilers Required)
- 250 PSI Rated
- Repairable Air Cylinder with a removable Rod Cartridge
- 1 1/2" to 24" Bore Sizes
- All NFPA mounting styles, piston rod diameters and thread sizes available
- All cylinder special options and features available
- MH Cylinders may also be custom designed to suit specific customer applications

Click to enlarge

Features and Advantages

View Dimensional Charts

Accessories and Repair Services are available. Call us Today.

» DIMENSIONAL CHARTS
Looking for a specific mounting type? Click Here.

Ordering Information

HOW TO ORDER MODEL MH:
For your convenience, please refer to the 'How to Order Brochure'. Just follow steps A thru J in the example creating your Cylinder Callout No.

- We would like to give you two easy ways to view our 'How to Order Brochure'.
- **Quick View**--(Brochure will be viewed in a side-by-side format.)
 - **Printable Version**--(Brochure will be viewed in a single page format.)
 - **Click here to place order or request quote**

Features	Advantage	Benefit
1. Heads and Caps	Square, precision-machined steel. Assures concentricity of tube, bearing, cushion and piston rod.	Can be made proximity switch ready to accept same probe-length switches at each end without spacers.
2. Cylinder Tube	D.O.M. seamless 1020 to 1026 steel; precision honed to 12/15 micro inch finish; hard chrome plated .0003/.0005" thick on ID.	Resists wear, corrosion and dents; reduces wear on piston seals.
3. Wear Band	Delrin™ material.	Creates low friction, long lasting wear surface which prevents scoring of cylinder tube inner wall.
4. Lubrication Reservoirs	Located underneath wear band inside piston and also inside	Provides effective way of metering maximum amount

Shortcut to: Peninsular's Cylinder Configurator

Fast Simplified Cylinder Ordering !

Important Configurator Information !

Our model MH cylinder configurator will provide our customers with significant cost savings because it eliminates the complexities and reduces the time associated with the engineering and ordering process.

Contact Us Today
Peninsular Cylinder Co.
27650 Groesbeck Hwy.
Roseville, MI 48066

» Toll Free: 800-526-7968 » Phone: 586-775-7211
» Fax: 586-775-4545

Need Cylinders Repaired?
Ask The Cylinder Doctor

OVER 50 YEARS EXPERIENCE

ISO 9001:2000 REGISTERED

	the bearing cartridge.	of lubricant to all areas over long time period. Not subject to air turbulence and contamination.
5. Lubricant (not shown)	Teflon™ based grease.	Long lasting lubrication of piston seals, inner cylinder wall surface and rod bearing cartridge seals and ID.
6. Piston	PistonOne-piece steel, black oxidized with uniform cushion hubs on both sides, threaded onto piston rod, staked and secured with Loc-Tite™.	Prevents rusting and air leakage; anchored onto piston rod with minimum undercut providing maximum strength. Additional pinning onto rod optional.
7. Tube Seals	Buna-N Nitrile axial placed O-Rings.	When combined with accurately torqued tie rods, prevents extrusion of seal and air leaks under pressure.
8. Cushion Adjustment Screw	Steel needle valve with Buna-N O-ring sealed screw, held captive with locking snap ring.	Accurate fine adjustment of cushioning speed; no air leakage and safe for all users due to internal captive screw.
9. Rod Seal	80 durometer, rounded lip, pre-lubricated, carboxylated nitrile cup style. Smears grease through ID of rod cartridge extending seal life within.	Resists abrasion; significantly increases life and prevents leakage around piston rod.
10. Rod Wiper	80 durometer, sharp double lip, pre-lubricated, carboxylated nitrile seal.	Provides additional sealing benefit beyond the rod seal. Inside edge always lubricated extends life significantly, prevents dirt and grit from entering bearing and cylinder.
11. Piston Rod	High yield strength steel, case hardened OD to 50-55 RC. Core hardness to 28-34 RC. Hard chrome plated .0003/.0005" thick and polished to 12/15 micro inch finish. Rolled threads.	Resists wear. All NFPA rod and thread sizes, including female and studded male ends available, plus metric threads. Provides positive connections to existing machine components.
12. Bearing Cartridge	Floating, self-aligning in either ductile iron or SAE 660 bronze with internal lubrication reservoir. Special "Slip Tuff" coated cartridge is also available for heavy side loaded applications. Retained by plate with cap screws; strong and shock resistant. A Buna-N O-ring located around the cartridge OD prevents leakage.	Float condition minimizes piston rod misalignment by reducing side loading. ID of bearing cartridge, rod seal and rod wiper lubricated on each stroke, reducing wear. Easily removed for maintenance without special tools to disassemble cylinder. Optional "Slip Tuff" bearing provides lubricative wear surface with hardness characteristics that significantly reduce galling and bearing cartridge failure under severe side loaded operating conditions.
13. Tie Rods	Made from 100,000 psi minimum yield, stress-proof, medium carbon steel with rolled threads at each end.	Provides maximum strength for connecting cylinder mounts and used with lock nuts to prevent loosening in service. Accurate torquing prevents leaks at tube seals.
14. Cushion Hubs	Steel with 8/12 micro inch finish RMS. Black oxidized to prevent rusting and corrosion.	Uniform on each side of piston to eliminate different size cushion seals and reduce spare parts inventory. Smooth surface stops cushion seal wear and provides air-tight accurate operation. Ideal for proximity switch applications.
15. Piston Seals	80 durometer, rounded lip, pre-lubricated, carboxylated nitrile U cups.	Resists abrasion; when used with Peninsular's internal lubrication system, provides considerably less

16. Cushion Seals	90 durometer floating check type Urethane seals eliminate ball checks and related parts.	wear and increases operating life. Low friction breakaway and 100% air-tight cushioning assures smooth maximum effectiveness. Metal to metal cushions are eliminated and same size seals at each end reduce parts inventory.
17. Ports	NPT standard, SAE O-ring optional.	Metric and other thread size options. Universally adaptable to any hose or fitting.
18. Optional Proximity Switch Capability (not shown)	Allows for non-contact piston position sensing at near end of stroke. Precision machined cylinder heads and piston cushion hubs allow for in-port mounting of "RF inductive" proximity switches using the same switch probe length at each cylinder end without shims or spacers underneath the switch.	Self-contained switch probe not subject to contamination. This patented design creates the same air gap between the sensing probe and target (cushion hubs), thus providing consistent, reliable and repeatable stroke-to-go. Eliminates the design and construction of brackets necessary to mount mechanical limit switches. US Pat. No. 4,726,282 & D 295,753

[BACK TO TOP](#)

Field Service and Engineering Support

We understand the importance of technical assistance and the availability of products and repair parts. That's why we have a distributor network and technical representatives throughout the country. You can also reach our Customer Service Department for help.

Complete Repair Facility

Peninsular repairs all air and hydraulic cylinder makes and models. All cylinders are performance tested before shipment. Estimates are provided prior to repair activity.

Easy Order Procedure

For your convenience, please refer to the "How to Order and Specify Section". Just follow steps A thru J in the example and forward to us for price and delivery information or contact our Customer Service Department or your Authorized Peninsular Distributor.

For Near End of Stroke Position Sensing

Improved Optional Proximity Switch Capability In-Port cylinder head mounted proximity switch Design allows for the use of the same switch probe length at both ends WITHOUT SPACERS UNDERNEATH THE SWITCH. May be used as an air supply port if a switch is not required. U.S. Patent No. 4,726,282 & D295,753



RF Inductive (In-Port Mounted) Proximity Switch Probe Length Dimensions (Both cylinder heads)										
Bore Size:	1 1/2"	2"	2 1/2"	3 1/4"	4"	5"	6"	8"	10"	12"
Probe Length:	1.025	1.025	1.025	1.025	1.250	2.062	2.062	2.875	3.775	4.562

[BACK TO TOP](#)

[Home](#) | [Dimensional Charts](#) | [Product Info Sheets](#) | [Cylinder Accessories](#) | [Cylinder Repair Division](#) | [Ford and Chrysler Standard Cylinders](#) | [Air Powered Clamps](#) | [Pneumatic Thrusters \(Slides & Die Lifters\)](#) | [Special Cylinders](#) | [About Us](#) | [Sitemap](#) |

Toll Free: 800-526-7968 Phone: 586-775-7211 Fax: (586) 775-4545

© 2002-2004 Copyright Peninsular Cylinder Co. All Rights Reserved

Developed by [Miller Media Inc.](#) 248-528-3600