







All Simplex hoses have 3/8" male NPTF threads, and include end guards as standard equipment. Special lengths are available upon request.







- **H & HC Series** industrial grade 1/4" I.D. hose is rated at **10,000 psi operating pressure and 20,000 psi minimum burst pressure**. This hose is the recommended choice for hand pump & cylinder sets, as well as a wide range of other intermittent applications.

Model Number	Length (Ft.)	Hose End	Hose End	I.D. (in)
H3	3			1/4
H6	6			
H10	10			
H20	20			
H36	36			
H50	50	3/8" NPTF Male	3/8" NPTF Male	
HC3	3			
HC6	6			
HC10	10			
HC20	20			
HC36	36	3/8" NPTF Male	C213 Coupler*	
HC50	50			

\*All hoses with couplers includes CR215 Dust Cap.



- **High Flow HD & HDC Series 3/8" I.D.** hose is recommended to achieve higher retraction speeds and minimal flow restrictions. These heavy duty hoses are rated at **10,000 psi with a minimum burst pressure of 30,000 psi**.

<i>Model Number</i>	<b>Length (Ft.)</b>	<b>Hose End</b>	<b>Hose End</b>	<b>I.D. (in)</b>
<i>HD3</i>	3			3/8
<i>HD6</i>	6			
<i>HD10</i>	10			
<i>HD20</i>	20			
<i>HD50</i>	50	3/8" NPTF Male	3/8" NPTF Male	
<i>HDC3</i>	3			
<i>HDC6</i>	6			
<i>HDC10</i>	10			
<i>HDC20</i>	20			
<i>HDC50</i>	50	3/8" NPTF Male	C213 Coupler*	
				
		C213 Coupler*	C213 Coupler*	

\*All hoses with couplers includes CR215 Dust Cap.

Note: Recommended for use with Suc-O-Matic Pumps.



In this fixed outdoor application Simplex hand pumps and hoses are permanently attached to this mineral processing machine. "The desert environment is tough on hydraulic equipment. Simplex gives us the reliability we need."