



AIR CYLINDERS

HYDRAULIC CYLINDERS

- NFPA STEEL HEAVY DUTY
- NFPA ALUMINUM MED DUTY
- METRIC STEEL HEAVY DUTY
- METRIC ALUMINUM MED DUTY
- NFPA HIGH PRESSURE
- NFPA LOW PRESSURE
- METRIC HIGH PRESSURE

- DIMENSIONAL CHARTS
- PRODUCT INFO SHEETS
- CYLINDER ACCESSORIES
- CYLINDER REPAIR DIVISION
- FORD & DAIMLER CHRYSLER STANDARD CYLINDERS
- AIR POWERED CLAMPS
- PNEUMATIC THRUSTERS (SLIDES & DIE LIFTERS)
- SPECIAL CYLINDERS
- ABOUT US

- Request Product Literature
- Request Catalog on Disk
- Request Quote

When the pressure is on,  
You can count on Peninsular!



HOME EMAIL US SITEMAP

HYDRAULIC CYLINDERS  
Click links below to view pages in this section

- NFPA High Pressure
- NFPA Low Pressure
- Metric High Pressure

Cylinder Warranties

- Hydraulic Cylinders
- Pneumatic Cylinders
- Custom Cylinders

Hydraulic Cylinders

NFPA High Pressure Hydraulic Cylinder-Model HP



Click to enlarge

Heavy Duty High Pressure NFPA Hydraulic Cylinders

3,000 PSI Working Pressure

- Designed To Survive In Destructive Applications
- Repairable Hydraulic Cylinder with a removable Rod Cartridge
- 1 1/2" to 24" Bore Sizes
- All NFPA mounting styles, piston rod diameters and thread sizes available
- All cylinder special options and features available
- HP Cylinders may also be custom designed to suit specific customer applications.

- Features and Advantages
- View Dimensional Charts

Accessories and Repair Services are available. Call us Today.



Ordering Information

HOW TO ORDER MODEL HP:  
For your convenience, please refer to the 'How to Order Brochure'. Just follow steps A thru J in the example creating your Cylinder Callout No.

We would like to give you two easy ways to view our 'How to Order Brochure'.

- Quick View--(Brochure will be viewed in a side-by-side format.)
- Printable Version--(Brochure will be viewed in a single page format.)
- Click here to place order or request quote

Features	Advantage	Benefit
1. Heads and Caps	Square, precision-machined steel.	Assures concentricity of tube, bearing, cushion and piston rod. Chamfered grooves allow fast and easy positioning of cylinder tube over the tube seals. Can be made proximity switch ready to accept same probe-length switches at each end without spacers.
2. Cylinder Tube	Heavy wall seamless D.O.M. steel material (1020 to 1026). Precision honed to 10/15 micro inch finish and hard chrome plated .0003/.0005 thick on I.D.	Reduces wear on piston seals and tube surface. <b>Hard chrome I.D. finish provides corrosion resistance and minimizes tube scoring.</b>
3. Piston	One-piece fine grained ductile iron piston is threaded onto piston rod, torqued with a jam nut and held in place with Loc-Tite. Piston can be pinned onto rod as an option. Holes are drilled in each side of piston face, when U-Cups are used, to	Wide piston bearing surface reduces bearing loads and assures low wear and low friction to the piston seals and tube ID. An O-Ring with two Teflon backups are used to seal the piston to the rod, which prevents fluid leaks from

Shortcut to:  
Peninsular's  
Cylinder  
Configurator

Fast  
Simplified  
Cylinder  
Ordering !

Important  
Configurator  
Information !

Our model HP cylinder configurator will provide our customers with significant cost savings because it eliminates the complexities and reduces the time associated with the engineering and ordering process.

Contact Us Today  
Peninsular Cylinder Co.  
27650 Groesbeck Hwy.  
Roseville, MI 48066  
Toll Free: 800-526-7968  
Phone: 586-775-7211  
Fax: 586-775-4545



OVER 50 YEARS  
EXPERIENCE

ISO 9001:2000  
REGISTERED

	allow fluid pressure to increase the positive sealing.	bypassing the piston.
4. Tie Rods	Made from 100,000 psi minimum yield, stress-proof, medium carbon steel with rolled threads at each end.	Provides maximum strength for connecting cylinder mounts. Lock nuts prevent loosening in service. Accurate torquing prevents leaks at tube seals.
5. Tube Seals	90 durometer Buna-N Nitrile O-Rings are seated into grooves in both the head end and cap end covers. O-Rings are backed up with Teflon rings which effectively prevent O-Ring extrusion under pressure.	When combined with accurately torqued pre-stressed tie rods, proper O-Ring placement at the ID of the tube and confinement of the tube OD, seal extrusion and fluid leakage under pressure is prevented.
6. Rod Seal	The symmetrical loaded rod seal is made from 80 durometer Nitrile with an attached urethane anti-extrusion heel. A Delrin retainer holds the seal in place and is positioned in a groove between the head and bearing cartridge.	Provides positive static and dynamic sealing at both low and high pressures. Anti-extrusion heel energizes sealing mechanism as pressure increases. Greater tolerance for side loading and increased stability is provided in high pressure applications.
7. Rod Wiper	80 durometer, sharp double lip, pre-lubricated, carboxylated Nitrile seal provides additional sealing beyond rod seal. Additional materials can be used to combat various application demands, such as high heat. Severe external conditions could require the addition of a metallic rod scraper installed ahead of the rod wiper to effectively provide dual protection from the elements.	Prevents dust, dirt and grit from entering the bearing cartridge and cylinder, which significantly extends the cylinder life.
8. Piston Rod	100,000 psi minimum yield strength induction hardened and chrome plated steel with core hardness of RC 28-34. Case hardened to RC 50-55. Rod is hard chrome-plated (.0003/.0005 thick) and polished to 12/15 micro inch finish. Solid male threads contain radiused undercut.	Resists wear. All NFPA and metric rod and thread sizes, including female and studded male ends, are available with rolled threads. Provides positive connections to existing machine components. Solid male threads with radiused undercut minimize rod end breakage.
9. Bearing Cartridge	Floating, self-aligning bearing cartridge is made from grade 65-45-12 ductile iron or 660 bronze as an option. Our optional "Slip Tuff" bearing cartridge is also available for heavy side loaded applications. Cartridge is retained by cap screws and plate providing for strength and shock resistance. 90 durometer Buna-N O-Ring with Teflon backup ring on the cartridge O.D. prevents extrusion and fluid leakage around the outside of bearing cartridge.	Float condition minimizes piston rod misalignment by reducing side loading. Optional "Slip Tuff" bearing cartridge provides lubricious wear surface with hardness characteristics that significantly reduce galling and bearing cartridge failure under severe side loaded operating conditions. Easily removed for rod seal and rod wiper maintenance without requiring special tools to disassemble the cylinder.
10. Ports	NPT or SAE O-Ring ports are to be identified at time of order. Optional port sizes include flange ports, metric ports and oversized ports.	Universally adaptable to any hose or fitting.
11. Piston Seals	80 durometer, pre-lubricated, sharp lip, carboxylated Nitrile U-Cups with Teflon backup rings are standard up to and including 8" bore. Hydraulic poly pak type seals are standard for 10" bore and larger cylinders. Poly pak seals may also be used on smaller bores as an option. Other high load piston seal configurations are also optionally	Teflon backup rings prevent U-Cups from extruding and minimize leakage. Hydraulic poly pak type seals also reduce seal failure for larger bore cylinders operating under stressful conditions. The T-Seal centered between the optional cast iron rings helps prevent leakage and the probability of seal failure during high shock

	available, including step cut cast iron piston rings, with a T-Seal centered in between, are also available as an option.	operating conditions. Piston sealing flexibility also exists to meet other high load destructive applications.
12. Cushions	Floating ductile iron rod cushion collar on head end. The cap cushion is a 660 bronze floating, check-type seal insert held captive by a retaining ring in the rear end cap. Ball checks are provided at both ends for rapid breakaway out of the cushion and the ball check screws are flush with the end caps.	Cushions are optional but ultimately help prevent cylinder failure, due to fatigue, resulting from the piston slamming into cylinder end caps. A reliable floating cushion system provides for smooth action and eliminates binding conditions, which can cause sudden failure.
13. Cushion Adjustment Screw	Steel needle valve with 90 durometer Nitrile O-Ring and Teflon backup ring. The captive adjustment screw can be locked in place and is flush with the end cap. The lock down mechanism prevents the screw from loosening due to vibration.	The Teflon backup ring behind the O-Ring prevents fluid leakage around the adjustment screw and helps ensure accurate fine adjustment of cushioning speed. Captive screw assures user safety.
14. Optional Air Bleed System (not shown)	Manual air bleed plug is located on the cylinder tube.	Eliminates trapped air from inside the cylinder.
15. Optional Rod Cartridge Drain Back System (not shown)	Drain feature is an additional groove cut into the front end of the bearing cartridge, between the rod wiper and rod seal, that drains off any accumulation of fluid between the seals. A cartridge drain port is located on the cartridge retainer plate for a user-installed drain line back to the reservoir.	Captures hydraulic fluid and drains it back to the reservoir. This minimizes the slow weepage of hydraulic fluid through the rod wiper onto the piston rod.

[BACK TO TOP](#) 

#### Field Service and Engineering Support

We understand the importance of technical assistance and the availability of products and repair parts. That's why we have a distributor network and technical representatives throughout the country. You can also reach our Customer Service Department for help.

#### For Near End of Stroke Position Sensing

Complete repair facility  
 Peninsular repairs all air and hydraulic cylinder makes and models tested before shipment. Estimates are provided prior to repair at cylinder head mounted proximity switch capability. Design allows for the use of the same switch probe length at both ends WITHOUT SPACERS UNDERNEATH THE SWITCH (order and Spacers for your convenience, please refer to the "How to Order" and Specifications in the example and forward to us for price and delivery info available. U.S. Patent No. 4,726,282 & 4,295,753  
 Service Department of your Authorized Peninsular Distributor.



[BACK TO TOP](#) 